#### LINEAR LIGHTING | STRIP SERIES

## NATIONAL SPECIALTY LIGHTING

XX: Length in feet; YY: Color temperature

BL: Blue

## **COB Indoor**

The COB indoor lights are designed for optimal performance, delivering uniform lighting ideal for a variety of settings including commercial spaces, retail environments, and homes.



#### **FEATURES**

- 1 Bin
- 2 Step MacAdam Ellipse
- 3oz PCB board
- 3M Adhesive
- Field cuttable every 50mm (2")
- Low power consumption
- Smooth luminance no hot spots
- Available in 20' (6.1m) and 100' (30.48m) spools (custom cuts available)
- 20' spools come with 6Ft pre-soldered power feeds
- Safe, 24V DC operation
- Fully dimmable with dimmable power supplies (sold separately)
- 6 years limited warranty

#### **APPLICATIONS**

- Aisle and stairway lighting
- Cabinet and cove lighting
- Back lighting
- Showcase lighting
- Linear decorative lighting

SPECIFICATIONS		
Product Code		LTP-XX-YY-COB-H90 and LTP-XX-YY-COB (XX: Length in feet; YY: Color temperature)
Electrical	Input Voltage	24V DC
	Power Consumption	4.2W/Ft
Specs	Color Temperature	2700/3000/3500/4000/6500K
	CRI	90+ for white color temperatures
	Lumen Output	315 Lumens per ft 2700K; 319 Lumens per ft 3000K; 328 Lumens per ft 3500K;
		336 Lumens per ft 4000K; 374 Lumens per ft 6500K
	Efficacy	75 LPW 2700K; 76 LPW 3000K; 78 LPW 3500K; 80 LPW 4000K; 89 PLW 6500K
	Dimmable	Yes
	Beam Angle	120°
LED	Туре	Chip on Board
	Life Span	50,000 Hours
	Spacing	2mm
	# per foot (304mm)	91
Design	Dimensions (Inches)	.39" W
	Dimensions (Millimeters)	10mm W
	Max Single Run Length	20Ft
	<b>Custom Cuttable</b>	2" (50mm)
	Approved Location	Indoor
Warranty	6 years	
Approvals	cETLus	

# 0.39" (100mm) 2444 2444 2444 2444 2444

#### **PRODUCT CODES**

20Ft spools

LTP - 20 - YY - COB - H90

LED TAPE LIGHT LED Color

2700K


3000K

3500K


4000K

6500K

BL: Blue







#### **ACCESSORIES**



LTP-001-HD-HP-6 72" Power feed connector for CCT indoor. Add "-O" for opposite end.



LMSII-001
Terminal block and junction box for connection to additional lengths of power cable if needed



BL: Blue

LTP-010-S Clear PVC mounting "U" channel



LV-SPIR-1CH-LV
PIR Motion Sensor, 1
Channel, 24V DC
NOTE: To be used with non dimmable drivers only

**NOTE**: See page 36-37 for the complete range of aluminum extrusions.

#### INDOOR/OUTDOOR DIMMABLE DRIVERS

#### TRE24L40DC

Max 8.6' (2.6m) Min 8 Watts, 1.9' (0.57M) LED COB Strip 6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

#### TRE24L96DC

Max 21.4' (6.5m) Min 8 Watts, 1.9'(0.57m) LED COB Strip 6.77" x 2.67" x 1.26" (171 x 68 x 32mm)

### NON DIMMABLE DRIVERS

#### LEDDR-24-120W

Indoor/Outdoor driver
Max 21.4' (6.5m) per single tap
Max 28' (8.5m) combined 2 secondary taps
Input: 100 - 240V AC
Output: 24V DC
10" x 3 3/8" x 3 3/16" (254 x 85.7 x 80.9mm)