



CONTROLLERS

3 in 1 LED Strip Controller	5-Channel High Performance Amplifier	4-Zone RGB+CCT Remote	8 Zone RGB+CCT Wall Panel Remote
CNTRL-RGBCCT	CNTRL-AMP	CNTRL-4Z-RGBCCT-RM	CNTRL-8Z-RGBCCT-WP

ACCESSORIES

Mounting Clips	Silicone Glue	1M Solid Mounting Extrusion
SL-RGBW-MC	NFLX-GLUE	SL-RGBW-EX-39

DRIVERS

Non-Dimmable

Plug-in Driver 48W/96W:	<ul style="list-style-type: none"> PGID2448 PGID2496
Indoor/Outdoor driver:	LEDDR-24-120W

Specifications

Input Voltage	24V DC	SDCM	<3
Power Consumption	<ul style="list-style-type: none"> 2.19W/ft (7.2W/m) for RGB 2.19W/ft (7.2W/m) for 3000K 	Lifespan	50,000 Hours
Efficacy	70Lm/w	Dimensions (Inches)	.37" W
Color Temperature	RGB + 3000K	Dimensions (Millimeters)	9.5mm W
Lumen Output	153Lm/ft (504Lm/m)	Max Length	40Ft (12M)
Beam Angle	160°	Custom Cuttable	2.19" (55.56mm)
Chip Type	2835RGB + 2219WW	IP Rating	IP67
CRI	90	Approved Location	Outdoor/Indoor
# per meter	252	Warranty	5 Years
Binning	1BIN	Approvals	cULus

Ordering Code(s)

- SL-OD-RGB30K-XX-BA8 [XX: Length in feet; BA: 2835+2219 LED; 8: 8mm PCB]
- Available in 20 feet: SL-OD-RGB30K-20-BA8

Project		Type	
Date		Contact	
Notes			