



ACCESSORIES	
6" Jumper	ST-10MM-BWBC-6
Splice	ST-10MM-B2BC
6' power feed	ST-10MM-W2BC-72

ACCESSORIES	
0/1~10V Dimming Controller	ST-10MM-BWBC-6

DRIVERS	
<b>Dimmable</b>	
Dimmable Electronic LED Driver:	<ul style="list-style-type: none"> <li>TRE24L40D</li> <li>TRE24L96DC</li> </ul>
Switchex	SX-24V-DD-100W
<b>Non-Dimmable</b>	
Plug-in Driver	<ul style="list-style-type: none"> <li>PGID2448</li> <li>PGID2496</li> </ul>
Indoor/Outdoor driver	LEDDR-24-120W

Specifications			
Input Voltage	24V DC	Binning	1BIN
Power Consumption	4.39W/ft (14.5W/m)	SDCM	<2
Efficacy	110Lm/w	Lifespan	50,000 Hours
Color Temperature	2700K and 3000K	Dimensions (Inches)	.39" W
Lumen Output	486Lm/ft (1595Lm/m)	Dimensions (Millimeters)	10mm W
Beam Angle	120°	Max Length	20Ft (6M)
Dimmable	Yes, via controllers	Custom Cuttable	1.97" (50mm)
Chip Type	2835	IP Rating	IP20
CRI	90	Approved Location	Indoor
# per meter	140	Warranty	5 Years

**Ordering Code(s)**

- ST-ID-27K-HP-XX-B0 [XX: Length in feet; B: 2835 LED; O: 10mm PCB] / Available in 20 feet: ST-ID-27K-HP-20-B0
- ST-ID-30K-HP-XX-B0 [XX: Length in feet; B: 2835 LED; O: 10mm PCB] / Available in 20 feet: ST-ID-30K-HP-20-B0

Project		Type	
Date		Contact	
Notes			